

PHY 117 HS2024

Today:


- standing sound waves
- spherical wave propagation
- interference patterns
- formula for interference

Week 12, Lecture 2


Dec. 4th, 2024

Prof. Ben Kilminster

Standing sound waves in a closed tube of length L



The pressure is an anti-node at both ends.




$$n=1 \quad L = \frac{1}{2} \lambda_1 \quad f_1 = \frac{v}{\lambda_1} = \frac{v}{2L}$$

$$n=2 \quad L = \lambda_2 \quad f_2 = \frac{v}{\lambda_2} = \frac{v}{L}$$

$$n=3 \quad L = \frac{3}{2} \lambda_3 \quad f_3 = \frac{v}{\lambda_3} = \frac{3}{2} \frac{v}{L}$$

← How do we understand these plots?





For $n=2$




In general, $L = \frac{n}{2} \lambda_n$ $f_n = \frac{v}{\lambda_n} = \frac{n v}{2L}$

so $\lambda_n = \frac{2L}{n}$ for $n=1, 2, 3, \dots$

Ruben's flame tube



Waves moving in 2 or 3 dimensions



lines \perp to wave fronts are called rays




Circular
Consider 2-D wave from a point source
(like throwing stone in water)

Energy moves in all directions uniformly

In 3-D, like sound waves, the wave moves spherically.

surface area of a 3-D sphere is $4\pi r^2$




$$\text{Intensity} = I = \frac{\langle \text{power} \rangle}{\text{area}} \leftarrow \text{average power}$$

Relationship between I and energy per unit volume

$$\eta = \frac{\epsilon}{V}$$

$$\Delta r = v \Delta t$$



The additional energy in this spherical shell of thickness Δr

$$\Delta \epsilon = \eta \underbrace{\Delta V}_{\text{Volume of shell}} = \eta \underbrace{A \Delta r}_{\Delta V} = \eta A v \Delta t$$

$$\text{Power} = \frac{\Delta \epsilon}{\Delta t} = \eta A v$$

$$\text{Intensity} = \frac{\text{Power}}{\text{area}} = \eta v$$

velocity of wave

$$\text{units} = \left[\frac{\text{W}}{\text{m}^2} \right]$$

energy density

We remember for a s.h.o., $E = \frac{1}{2} m \omega^2 A^2$

$$\Delta E = \frac{1}{2} \underbrace{\rho \Delta V}_{\rho \Delta V} \underbrace{\omega^2}_{\omega^2} \underbrace{A^2}_{S_0^2}$$

S_0^2 : maximal displacement

$$\Delta E = \frac{1}{2} \rho \Delta V \omega^2 S_0^2$$

$$\eta = \frac{\Delta E}{\Delta V} = \frac{1}{2} \rho \omega^2 S_0^2$$

$$I = \eta N = \frac{1}{2} \rho \omega^2 S_0^2 N$$

for sound waves: $P_0 = \rho \omega N S_0$


$$\text{so } S_0^2 = \frac{P_0^2}{\rho^2 \omega^2 N^2}$$

$$I = \frac{1}{2} \frac{P_0^2}{\rho N}$$

Intensity of sound waves
"How loud is something"

For 3-D waves:

$$I = \frac{\text{power}}{\text{area}} \leftarrow \text{for sphere: } 4\pi r^2$$



So Intensity decreases like $\frac{1}{r^2}$

If we know the intensity at r_1 ,
what is intensity at $2r_1$?

$$r_1 = r$$

$$r_2 = 2r$$


total power at $r_1 =$ total power at r_2

$$I_1(4\pi r_1^2) = I_2(4\pi r_2^2)$$



so if $r_2 = 2r_1$,

$$\text{then } I_2 = \frac{1}{4} I_1$$

Huygen's principle - a wave acts as if each point along the wave front is a spherical wave source.




← represents the wave front produced by all point sources along wave front.




(b) Each point on a wavefront is a new point source.

A plane wave is comprised of harmonic spherical waves






wave propagates as if from one point



Interference: wave superposition can lead to interference if waves of same λ + amplitude are out of phase by some angle $\Delta\phi = \delta$

14.5. INTERFERENCE

143



(a) If $\Delta\phi = 90^\circ$, there is destructive interference. (b) If $0^\circ < \Delta\phi < 90^\circ$, there is partial interference with amplitude $2A \cos \frac{\Delta\phi}{2}$. (c) If $\Delta\phi = 0^\circ$, there is constructive interference with amplitude $2A$.

Figure 14.11: Interference between two waves with the same wavelength λ and amplitude A , but phase difference $\Delta\phi$.

Adding 2 waves out of phase

general formula
(no derivation)

$$y_1 = y_0 \sin(kx - \omega t)$$

$$y_2 = y_0 \sin(kx - \omega t + \delta)$$

$\delta =$ phase shift
(angle)

$$y_1 + y_2 = 2y_0 \cos\left(\frac{1}{2}\delta\right) \sin\left(kx - \omega t + \frac{\delta}{2}\right)$$

Example
for pressure waves

$$P_1 = P_0 \sin(kx - \omega t)$$

$$P_2 = P_0 \sin(kx - \omega t + \delta)$$

$$P_1 + P_2 = 2P_0 \cos\left(\frac{1}{2}\delta\right) \sin\left(kx - \omega t + \frac{\delta}{2}\right)$$

One way to get a phase difference is to have different path lengths.

Sources are coherent.
Same k, ω, A , amplitude
in phase



receiving a signal here

phase difference

$$\delta = (kx_1 - \omega t) - (kx_2 - \omega t)$$

$$= kx_2 - kx_1 = k \Delta x$$

Since $k = \frac{2\pi}{\lambda}$, so


$$\delta = \frac{2\pi \Delta x}{\lambda}$$

phase difference
from 2
coherent
sources

If $\Delta x = n\lambda$, $n = 0, 1, 2, \dots$

then $\delta = 2\pi n$, and we get constructive interference.

2 sources coherently emitting waves



Interference:

constructive when $y_1 + y_2 = 2y_0$


destructive when $y_1 + y_2 = 0$

waves add together
Constructively
when peaks overlap

waves adding together
at valleys constructively

waves add destructively
(peak of one wave
+ valley of the other
wave.)


condition for constructive interference



$$\Delta r = r_2 - r_1 = 0\lambda, \lambda, 2\lambda, 3\lambda, \dots$$

then we get
Constructive interference

Here is a source emitting a spherical wave.
The distance between peaks is λ .




This is a s.h.o.

Here are 2 coherent sources: Same $\omega, k,$ in phase at source.




Along this line, where $r_1 = r_2$, the waves constructively interfere.

$$\Delta r = r_2 - r_1 = 0 \lambda = 0$$




At point 3, the 3rd peak of one wave adds with the 3rd peak of other wave.

Along this line, the waves constructively interfere.



Along this line,
 $\Delta r = 1\lambda$


At point a,
the 4th peak
of source 1
adds with
the 3rd
peak of
source 2.




Along these lines, the waves add constructively

$$\Delta r = n\lambda$$
$$n = 0, \pm 1, \pm 2, \dots$$

If we measure the sum of the waves along the green line, there will be constructive maxima at the intersection of the peaks from the 2 sources.



sources are a distance, a , apart




Calculate the location of the maxima. We measure at point P, at a distance, D.

2 coherent sources, a, apart.

$\Delta L =$ path difference from sources to point Y,
 $\Delta L = r_2 - r_1$

$$\tan \theta = \frac{y}{D}$$

If $D \gg a$, then we can use the small angle approximation:
 $\sin \theta \sim \tan \theta \sim \theta$ (radians)



From our small triangle

$$\sin \theta = \frac{\Delta L}{a}$$

$\uparrow \frac{y}{D}$



$$\frac{\Delta L}{a} = \frac{y}{D} \Rightarrow \Delta L = \frac{ya}{D}$$


There are interference maxima when $\Delta L = n\lambda$ $n=0, \pm 1, \pm 2, \dots$

so we can set $\Delta L = n\lambda = \frac{ya}{D} \Rightarrow$ $\frac{y_n}{a} = \frac{n\lambda D}{a}$ location of maxima


2
Sources

1
receiver





W110



W108

Ruben's flame tube - more understanding



$n=1$

oscillate

① ΔP ΔP is +

node

② ΔP

node

① → ② → ① ...

highest plane

$n=2$

① ΔP

node node

② ΔP

① → ② → ①

Extra!

For Ruben's flame tube:

For quiet sounds, ΔP of the gas $<$ P of the gas

Why is pressure higher at pressure nodes?

From Bernoulli's equation, gas flow is proportional to square root of the pressure difference between inside + outside tube.

$$\text{flow} \sim \sqrt{P_{\text{inside}} - P_{\text{outside}}}$$

(The flow of gas out of the pipe)

When $\Delta P_{\text{maximal}}$, anti-nodes produce lower flames (flow rate is lower)

When $\Delta P = 0$, nodes, flow rate is higher

Part of the cycle, pressure is higher than average but part is lower. On average

This is why pressure is higher at nodes:

$$\sqrt{P + \Delta P \text{ at anti-nodes}} < \sqrt{P + \Delta P \text{ at nodes}}$$